



TEREZ[®] PP



www.terplastics.com

 **TER** | plastics

Portfolio

TEREZ Polypropylene

Since its development in the 1950s, Polypropylene (PP) has seen numerous advancements and has found new applications across various industries. Polypropylene is known for its excellent chemical resistance, high impact strength, It also boasts a low density, making it a lightweight yet durable material.

Polypropylene is often reinforced with materials such as glass fibers to enhance its mechanical properties, including increased stiffness and strength. This reinforcement also allows PP to withstand higher continuous use temperatures. Depending on its formulation, PP can be used in environments ranging from -20°C to +100°C, with short-term exposure totemperatures up to 140°C.

One of the notable characteristics of Polypropylene is its resistance to moisture absorption, which helps maintain its mechanical properties in humid environments. This makes PP an ideal choice for applications where moisture resistance is crucial.


Due to its versatile properties, Polypropylene has replaced many traditional materials in various sectors. It is widely used in automotive parts, electrical components, and packaging. Typical applications include automotive bumpers, battery cases, and interior trim, as well as containers, pipes, and household goods.

Polypropylene's combination of lightweight, durability, and resistance to chemicals and moisture makes it a valuable material in modern manufacturing and engineering.



Nomenclature

Polymer Nomenclature		VW	Position 1	Raw material sources		Position 2	Visc MVR (230°C/2,16 kg)	cm3/ 10 min				
PPH	PP HOMO	GK1C	100	Chemical Recycling		TEREZ PPC 500	MVR 0 - 1	0,5				
PPC	PP COPO	GK1B	200	Bio based		TEREZ PPC 510	MVR 1 - 3	2				
PPR	PP RANDOM	GK1A	300	Prime Compound		TEREZ PPC 520	MVR 3 - 7	5				
Additional functional properties		GK3	400	Post Industrial Rezyclate		TEREZ PPC 530	MVR 7 - 13	10				
H	Various long-term heat stabilization systems for different requirements	GK4	500	Post Consumer Rezyclate		TEREZ PPC 540	MVR 10 - 20	15				
UV	Various long-term UV Resistance systems for different requirements	GK3+4	600	PIR + PCR		TEREZ PPC 550	MVR 15 - 25	20				
CA	Constant antistatic effect	Reinforcing Fiber / Filler						TEREZ PPC 560	MVR 25 - 35	30		
LM	Laser markable	G	Glass Fiber						TEREZ PPC 570	MVR 35 - 45	40	
SF	Super Flow Grades	GX	Flat Glass Fiber						TEREZ PPC 580	MVR 45 - 65	55	
CSM	Customer-specific modification / More than 3 additional functional properties	GL	Long Glass Fiber						Position 3		Range	%
MSR	Mar and scratch resistance	B	Glass Beads						501	5-15	10	
I	Impact modification	M	Mineral Filled						502	15-25	20	
		FR - System		UL 94	ISO 1043							
		FR2	HF HR	V-0	FR (51)							
		FR4	HF HR	V-2	FR (40)							
Approval		Flame retardant classification is thickness dependent										
MO	No LTDS	FR20	UL 94 V-0 until 0,4 – 0,6 mm						503	25-35	30	
W	Drinking water contact	FR21	UL 94 V-0 until 0,8 mm						504	35-45	40	
L	Food contact	FR22	UL 94 V-0 until 1,6 mm						505	45-55	50	
F1	Weather resistance / UL Certification	FR23	UL 94 V-0 until 3,2 mm						506	55-65	60	
								507	65-75	70		
								508	75-85	80		
								509	85-95	90		
								500	95-100	100		





Polymer Bases

Polypropylene (PP) is a widely used thermoplastic polymer, derived from the polymerization of the monomer propylene. Here are some key points about its polymer base:

- 1. Polymerization Process:** PP is typically produced through a process called chain-growth polymerization, using catalysts such as Ziegler-Natta or metallocene catalysts. This process allows for control over the polymer's molecular weight and structure.
- 2. Applications:** Due to its versatile properties, PP is used in a variety of applications, including packaging, automotive parts, textiles, and consumer goods. Its recyclability also makes it a popular choice for sustainable practices.

Polypropylene (PP) is a versatile polymer widely used in various applications. It is a thermoplastic polymer made from the monomer propylene. PP is known for its excellent chemical resistance. It is lightweight, durable, and can be easily molded into different shapes, making it ideal for packaging, automotive parts, textiles, and consumer goods. Additionally, PP is recyclable, contributing to its popularity in sustainable practices.

PP Portfolio

	Polypropylen Standard GF	Polypropylen High Performance GF	Polypropylen Standard Mineral Filled		Polypropylen Long Glass Fiber	Polypropylen Flame-Retardant
Unfilled	TEREZ PPC 300 E TEREZ PPH 300 E					TEREZ PPH 310 FR41 E TEREZ PPH 300 FR41 TEREZ PPH 430 FR41 TEREZ PPC 310 FR41 E TEREZ PPC 330 FR41
10% Filled	TEREZ PPC 330 G10 TEREZ PPH 330 G10 TEREZ PPH 439 G10	TEREZ PPH 330 H1 I1 G10 TR TEREZ PPH 340 G10 UV1	TEREZ PPH 340 MX10 TEREZ PPH 449 MX10			
20% Filled	TEREZ PPC 330 G20 TEREZ PPH 330 G20 TEREZ PPH 438 G20 TEREZ PPH 638 G20	TEREZ PPH 330 G20 UV1 TEREZ PPH 435 H20 G20 TEREZ PPH 435 H21 G20	TEREZ PPH 340 MX20 TEREZ PPH 445 MX20 TEREZ PPC 340 MX20			TEREZ PPH 330 G20 FR22 TEREZ PPH 435 G20 FR22
25% Filled	TEREZ PPH 330 G25 TEREZ PPC 330 G25					TEREZ PPH 330 G25 FR21 TEREZ PPH 330 G25 FR22 TEREZ PPH 330 G25 FR22 TEREZ PPH 435 G25 FR22
30% Filled	TEREZ PPC 330 G30 TEREZ PPH 330 G30 TEREZ PPH 340 G30 TEREZ PPH 437 G30 TEREZ PPH 637 G30 TEREZ PPH 639 G30	TEREZ PPH 330 H20 G30 TEREZ PPH 330 H21 G30 TEREZ PPH 435 H21 G30 LW TEREZ PPH 435 H20 G30 TEREZ PPH 435 H21 G30 TEREZ PPH 637 H2 G30	TEREZ PPH 340 MX30 TEREZ PPH 445 MX30 TEREZ PPC 340 MX20		TEREZ PPH 330 GL30 TEREZ PPH 330 H1 GL30 TEREZ PPH 435 H1 GL30	TEREZ PPH 330 G30 FR21 TEREZ PPH 330 G30 FR22 TEREZ PPH 435 G30 FR22
40% Filled	TEREZ PPH 320 G40 TEREZ PPH 436 G40	TEREZ PPH 433 H20 G40	TEREZ PPH 330 MX40		TEREZ PPH 330 GL40 TEREZ PPH 330 H1 GL40 TEREZ PPH 433 H1 GL40	
50% Filled	TEREZ PPH 320 G50 TEREZ PPH 425 G50	TEREZ PPH 320 H20 G50 TEREZ PPH 423 H20 G50 TEREZ PPH 523 H20 G50			TEREZ PPH 320 GL50 TEREZ PPH 325 H1 GL50 TEREZ PPH 423 H1 GL50	
60% Filled	TEREZ PPH 330 G60 TEREZ PPH 424 G60	TEREZ PPH 320 H20 G60 TEREZ PPH 423 H20 G60 TEREZ PPH 523 H20 G61			TEREZ PPH 320 GL60 TEREZ PPH 320 H1 GL60 TEREZ PPH 423 H1 GL60	

*ECO Grades in green

TER Plastics POLYMER GROUP

Alte Wittener Str. 50 · 44803 Bochum · Germany

P +49 (0)234 54154-0

F +49 (0)234 54154-333

info@terplastics.com

www.terplastics.com

All data, recommendations or pieces of information provided by TER HELL PLASTIC GMBH or on behalf of TER HELL PLASTIC GMBH are supported by research or experience and are believed to be reliable. For application, utilization, processing or other intended use of such information or products or the consequences thereof, TER HELL PLASTIC GMBH assumes no liability. The buyer is obliged to assure himself of the quality and all the features of the products. He takes full responsibility for the application, use and processing of our products and the use of the afore-mentioned information and for any consequences thereof. TER HELL PLASTIC GMBH shall not be held liable in whatever way for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the afore-mentioned information or products by the buyer.

ISSUE: OCTOBER 2025

